



SLC DL04 Round X1 R83 TED

10.06.2021

B_SLC1101



Product description

Retracted LED for creating comfortable ambient. Tilt-able (25°) round downlight with smooth design. Suitable for outside use (IP54). Available in black or white.

Retracted LED for creating comfortable ambient. Tilt-able (25°) round downlight with smooth design. Suitable for outside use (IP54). Quick connector with loop-in / loop-out. CRI>90 enhances vivid colours in any environment. Provides a lot of light (650-700lm).

Technical data

Suitable for built-in mounting	Yes
Suitable for suspended mounting	No
Adjustability	Swivelling
With light source	Yes
Surface protection	Powder coating
Voltage type	AC/DC
Type of control gear	LED operating device current-controlled
Dimming phase cut-off	Yes
Light distributor	Reflector
Beam angle	Medium beam 21-40°
Rated life time L80/B10 at 25 °C	50000 h
Protection class	II
Max. system power	10 W
Colour rendering index CRI	90-100
Width	95 mm

Suitable for wall mounting	No
Suitable for ceiling mounting	Yes
Lamp type	LED not exchangeable
Material housing	Aluminium
Material cover	Plastic, transparent
Nominal voltage	220 - 240 V
Control gear included	Yes
Reflector	High-gloss
Light sharing	Symmetric
Light outlet	Direct
Degree of protection (IP)	IP54
Rated ambient temperature according to IEC	-10 - 40 °C
Colour of light	White
Power factor	0,9
Height/depth	55 mm



Outer diameter	95 mm
Built-in height/depth	55 mm
Type of wiring	Suitable for through wiring
Conductor cross section	0,35 mm²
Connection type	Plug clamp
Strain relief	True
Beam angle (°)	36
Operating temperature	-10°C ~ +45°C
Dimming method	Trailing edge
Type of control signal	Trailing Edge
Brand	SLC
HS Code	94051040

Built-in width	83 mm
Built-in diameter	83 mm
Number of poles	3
Connectable conductor cross section	0,75 - 2,5 mm²
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index (CRI/Ra)	90
Tilt-able (°)	25
Cut-out hole (Ø: mm)	83
Dimmable	Yes
Dimming range	1-100%
Produced by	The Light Group